
Geberit Mapress ball valve, NPW, with actuator lever



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For compressed air (oil purity class 0–3)
- For installations with Geberit Mapress Carbon Steel
- For installations with Geberit Mapress Copper

CHARACTERISTICS

- Ball made of brass, chrome-plated
- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Operating temperature	-20 – +120 °C
Product material	Brass CW617N

INFO

- The ball valves are marked with PN 10 on the body in accordance with DVGW and EN 13828
- The ball valves are approved for up to PN 16

Art. no.	DN	DNV	d, ø mm	L cm	L1 cm	L2 cm	Z cm	Z1 cm	PN bar
94922	12	15	15	7.7	4.4	8.5	1.7	2.4	16
94923	15	15	18	8	4.4	8.5	1.7	2.4	16
94924	20	20	22	8.9	5.2	10.6	2.1	2.9	16
94925	25	25	28	9.6	5.6	10.6	2.4	3.1	16

Art. no.	DN	DNV	d, ø mm	L cm	L1 cm	L2 cm	Z cm	Z1 cm	PN bar
94926	32	32	35	10.9	6.1	10.6	2.7	3.4	16
94927	40	40	42	14.1	7.9	15.5	3.6	4.5	16
94928	50	50	54	15.7	9.4	17.5	3.9	4.8	16