
Geberit Mapress Carbon Steel system pipe, plastic-jacketed



Example image

APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Outside zinc-plated and plastic-jacketed
- Plastic jacketing made of PP, white

TECHNICAL DATA

Product material	Non-alloy steel 1.0034 E195 (EN 10305)
Surface roughness	10 µm
Thermal expansion	0.012 mm/(m·K)
Thermal conductivity, pipe	60 W/(m·K)
Specific thermal capacity	500 J/(kg·K)

ACCESSORIES

- Geberit Mapress pipe cutter R
- Geberit Mapress stripping tool
- Geberit Mapress stripping tool
- Geberit Mapress pipe deburrer
- Geberit Mapress insertion distance template with marker pen

Art. no.	DN	d, ø mm	di, ø mm	D cm	s1 mm	s mm	L m
19201	10	12	9.6	1.4	0.9	1.2	6
19202	12	15	12.6	1.7	0.9	1.2	6
19203	15	18	15.6	2	0.9	1.2	6
19204	20	22	19	2.4	0.9	1.5	6

Art. no.	DN	d, ø mm	di, ø mm	D cm	s1 mm	s mm	L m
19205	25	28	25	3	0.9	1.5	6
19206	32	35	32	3.7	0.9	1.5	6
19207	40	42	39	4.4	0.9	1.5	6
19208	50	54	51	5.6	0.9	1.5	6