
Geberit system pipe, ML, Therm, in coils





Example image

APPLICATION PURPOSES

- For Geberit FlowFit
- For Geberit PushFit
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For compressed air (oil purity class 0–3)
- For inert gases (e.g. nitrogen)

CHARACTERISTICS

- Inherently stable
- Can be bent by hand
- Forms a barrier against diffusion
- White exterior
- Pipe end with transparent protection plug

TECHNICAL DATA

Product material	PE-RT II / Al / PE-RT II
Surface roughness	7 µm
Thermal expansion	0.026 mm/(m·K)
Thermal conductivity, pipe	0.41 W/(m·K)

ACCESSORIES

- Geberit pliers
- Geberit pipe cutter ML
- Geberit FlowFit calibration tool

Art. no.	DN	d, ø mm	di, ø mm	s mm	L m
These articles are suitable for the following system: **Radiant heating and cooling**					
619.130.00.1	12	16	12	2	120
619.131.00.1	12	16	12	2	250

Art. no.	DN	d, ø mm	di, ø mm	s mm	L m
619.133.00.1	15	20	16	2	100
These articles are suitable for the following system: **Geberit FlowFit**					
619.130.00.1	12	16	12	2	120
619.131.00.1	12	16	12	2	250
619.133.00.1	15	20	16	2	100
619.135.00.2	20	25	20	2.5	50
These articles are suitable for the following system: **Geberit PushFit**					
619.130.00.1	12	16	12	2	120
619.131.00.1	12	16	12	2	250
619.133.00.1	15	20	16	2	100
619.135.00.2	20	25	20	2.5	50