
Geberit FlowFit 90° bend adaptor with male thread, long


Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For treated water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap
- Thread with transparent protective cap

TECHNICAL DATA

Product material	Lead-free gunmetal

Art. no.	DN	d, ø mm	R "	arc °	L cm	H cm	Z cm
620.522.00.1	12 / 15	16	1/2	90	5.7	3.7	2.4
620.523.00.1	12 / 20	16	3/4	90	6	4.5	2.7
620.524.00.1	15	20	1/2	90	6.1	3.7	2.8
620.525.00.1	15 / 20	20	3/4	90	6	4.5	2.7

Art. no.	DN	d, ø mm	R "	arc °	L cm	H cm	Z cm
620.526.00.1	20	25	3/4	90	6	4.5	2.7
620.527.00.1	20 / 25	25	1	90	6.3	5.6	3
620.528.00.1	25	32	1	90	6.8	5.6	3.2