
Geberit FlowFit coupling





Example image

APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For treated water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- O-ring made of EPDM
- Pressing connector with transparent protective cap

TECHNICAL DATA

Product material	PPSU

Art. no.	DN	d, ø mm	L cm	Z cm
620.010.00.1	12	16	7.7	1.2
620.011.00.1	15	20	7.7	1.2
620.012.00.1	20	25	7.7	1.2
620.013.00.1	25	32	8.7	1.5

Art. no.	DN	d, ø mm	L cm	Z cm
620.014.00.1	32	40	8.7	1.5
620.015.00.1	40	50	14.1	2.2
620.016.00.1	50	63	15.1	2.4
620.017.00.1	65	75	15.1	2.4