
Geberit FlowFit long coupling





Example image

APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For treated water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For creating additional connections in existing pipelines
- For connecting prefabricated pipe sections with length compensation
- For technical building systems, industry and shipbuilding
- For repairing damaged Geberit system pipes ML

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap

TECHNICAL DATA

Product material	Lead-free silicon bronze

Art. no.	DN	d, ø mm	L cm	Z cm
620.020.00.1	12	16	20–29.3	13.5–22.8
620.021.00.1	15	20	20–29.3	13.5–22.8
620.022.00.1	20	25	20–29.3	13.5–22.8

Art. no.	DN	d, ø mm	L cm	Z cm
620.023.00.1	25	32	22.1–32.1	15.1–25.1
620.024.00.1	32	40	23.4–34.2	16.3–27.1
620.025.00.1	40	50	33.8–49.5	22–37.7