
Geberit FlowFit bend adaptor 90° with male thread



Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For treated water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap
- Thread with transparent protective cap

TECHNICAL DATA

Product material	Lead-free gunmetal

Art. no.	DN	d, ø mm	R "	arc °	L cm	H cm	Z cm
620.510.00.1	12 / 15	16	1/2	90	5.7	2.5	2.4
620.520.00.1	12 / 20	16	3/4	90	6	3.1	2.7
620.511.00.1	15	20	1/2	90	6.1	2.8	2.8
620.521.00.1	15 / 20	20	3/4	90	6	2.7	2.7

Art. no.	DN	d, ø mm	R "	arc °	L cm	H cm	Z cm
620.502.00.1	20	25	3/4	90	6	2.9	2.7
620.512.00.1	20 / 25	25	1	90	6.3	3.2	3
620.503.00.1	25	32	1	90	6.8	3.1	3.2
620.504.00.1	32	40	1 1/4	90	7.3	4.2	3.7
620.505.00.1	40	50	1 1/2	90	10.4	4.7	4.5
620.506.00.1	50	63	2	90	11.7	5.8	5.4