
Geberit FlowFit bend adaptor 90° with female thread



Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For treated water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap
- Thread with transparent protection plug

TECHNICAL DATA

Product material	Lead-free gunmetal

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	Z cm	Z1 cm
620.540.00.1	12 / 15	16	1/2	90	6.1	2.2	2.8	0.9
620.550.00.1	12 / 20	16	3/4	90	6.3	2.5	3	1.2
620.541.00.1	15	20	1/2	90	6.1	2.4	2.8	1.1
620.551.00.1	15 / 20	20	3/4	90	6.5	2.6	3.2	1.3

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	Z cm	Z1 cm
620.532.00.1	20	25	3/4	90	6.5	2.8	3.2	1.5
620.542.00.1	20 / 25	25	1	90	6.9	3	3.6	1.4
620.533.00.1	25	32	1	90	7.4	3.4	3.8	1.8
620.534.00.1	32	40	1 1/4	90	8.1	3.7	4.5	2.2
620.535.00.1	40	50	1 1/2	90	11.2	4.5	5.3	3
620.536.00.1	50	63	2	90	12.8	5.3	6.4	3.5