
Geberit FlowFit connection bend 90°



Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Three fastening points
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap
- Thread with transparent protection plug

TECHNICAL DATA

Product material	Lead-free gunmetal

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	l cm	l1 cm	Z cm
620.750.00.1	12	16	3/8	90	3.6	6	1.9	1.3	2.7
620.760.00.1	12	16	1/2	90	3.6	6	1.9	1.3	2.8
620.751.00.1	15	20	3/8	90	3.6	6	1.9	1.3	2.7
620.761.00.1	15	20	1/2	90	3.6	6.3	1.9	1.3	3.1

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	l cm	l1 cm	z cm
620.800.00.1	12	16	3/8	90	5.2	6	1.9	1.5	2.7
620.810.00.1	12	16	1/2	90	5.2	6	1.9	1.5	2.7
620.801.00.1	15	20	3/8	90	5.2	6	1.9	1.5	2.7
620.811.00.1	15	20	1/2	90	5.2	6	1.9	1.7	3.1
620.821.00.1	15	20	3/4	90	5.2	6.3	1.9	1.9	3
620.802.00.1	20	25	3/4	90	5.2	6.7	1.9	1.9	3.4
620.770.00.1	12	16	1/2	90	7.8	6.8	1.9	3	3.5
620.771.00.1	15	20	1/2	90	7.8	7.3	1.9	3	4