
Geberit FlowFit adaptor union with female thread





Example image

APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For rainwater with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap
- Thread with transparent protection plug
- Flat gasket made of fibre composite material

TECHNICAL DATA

Product material	Lead-free silicon bronze

Art. no.	DN	d, ø mm	Rp "	G "	L cm	Z cm	SW mm
620.600.00.1	12 / 15	16	1/2	3/4	7.9	3.3	30
620.601.00.1	15	20	1/2	3/4	8.5	3.9	30
620.602.00.1	20	25	3/4	1	9.2	4.4	38
620.603.00.1	25	32	1	1 1/4	9.4	4.1	46

Art. no.	DN	d, ø mm	Rp "	G "	L cm	Z cm	SW mm
620.613.00.1	25 / 32	32	1 1/4	1 1/4	10.6	5.1	46
620.604.00.1	32	40	1 1/4	1 1/2	10.9	5.4	55
620.614.00.1	32	40	1 1/2	1 1/2	11.2	5.6	55
620.605.00.1	40	50	1 1/2	1 1/2	13.8	5.9	55
620.615.00.1	40 / 50	50	2	2	14.9	6.6	67
620.606.00.1	50	63	2	2 3/4	13.3	4.3	89