
Geberit FlowFit adaptor union with clamping ring





Example image

APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For copper pipes, rough, nickel-plated or chrome-plated
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Lead-free
- O-ring made of EPDM
- Pressing connector with transparent protective cap

TECHNICAL DATA

Product material	Lead-free silicon bronze

SCOPE OF DELIVERY

- Clamping ring union

Art. no.	DN	d, ø mm	d1, ø mm	L cm	l cm	z cm
620.680.00.1	12 / 10	16	12	5.8	1.7	0.8
620.683.00.1	12 / 10	16	14	5.8	1.7	0.8
620.690.00.1	12	16	15	5.8	1.6	0.9
620.691.00.1	12	16	16	5.8	1.6	0.9

Art. no.	DN	d, ø mm	d1, ø mm	L cm	l cm	z cm
620.681.00.1	15 / 12	20	15	6	1.6	1.1
620.684.00.1	15	20	18	6	1.6	1.1