


# Geberit Mapress CuNiFe ball valve with actuator lever, flanged






Example image

## APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For compressed air (oil purity class 0–3)

## CHARACTERISTICS

- Valve made of CrNiMo steel
- Spindle caulk made of PTFE
- Section seal of flange and ball made of PTFE
- Fulfils requirements in accordance with TA Air VDI 2440
- Connecting flange for motor in accordance with EN ISO 5211 (only for d = 76.1–108 mm)
- Length-adjustable actuator lever (only for d = 108 mm)
- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

## TECHNICAL DATA

| | |
|---|---|
| Operating temperature | -20 – +120 °C |
| Product material | CuNi10Fe1.6Mn, material no. 2.1972.11 |

## ACCESSORIES

- Actuator lever set, lockable, for Geberit Mapress ball valve, flanged

| Art. no. | DN | DNV | d, ø mm | k mm | m mm | L cm | L1 cm | L2 cm | Z cm | PN bar |
|---|---|---|---|---|---|---|---|---|---|---|
| **92120** | 12 | 15 | 15 | | | 12.2 | 5 | 9.3 | 4.1 | 13 |
| **92122** | 20 | 20 | 22 | | | 13.3 | 5.6 | 10.3 | 4.5 | 13 |
| **92123** | 25 | 25 | 28 | | | 14.2 | 6.6 | 12.8 | 4.8 | 13 |

| Art. no. | DN | DNV | d, ø mm | k mm | m mm | L cm | L1 cm | L2 cm | Z cm | PN bar |
|---|---|---|---|---|---|---|---|---|---|---|
| **92124** | 32 | 32 | 35 | | | 17 | 7.5 | 12.8 | 5.9 | 13 |
| **92125** | 40 | 40 | 42 | | | 19.4 | 8.5 | 15.8 | 6.7 | 13 |
| **92126** | 50 | 50 | 54 | | | 22.1 | 9.6 | 15.8 | 7.5 | 13 |
| **92127** | 65 | 65 | 76.1 | 70 | 9 | 29.1 | 13.5 | 22.3 | 9.2 | 10 |
| **92128** | 80 | 80 | 88.9 | 70 | 9 | 33.3 | 14.5 | 35.8 | 10.6 | 10 |
| **92129** | 100 | 100 | 108 | 102 | 11 | 41.2 | 17.7 | 50 | 13.1 | 10 |