
Geberit Mapress CuNiFe bend adaptor 90° with female thread





Example image

APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 0–3)
- For inert gases (e.g. nitrogen)
- For industry and shipbuilding
- For negative pressure

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	CuNi10Fe1.6Mn, material no. 2.1972.11

ACCESSORIES

- Fastening for Geberit Mapress elbow adaptor 90°

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	Z cm	Z1 cm
67503	12 / 15	15	1/2	90	3.8	7.4	1.8	6.1
67506	20 / 15	22	1/2	90	4.7	8.4	2.6	7.3
67507	20	22	3/4	90	4.7	8.6	2.6	7.1
67508	25	28	1	90	5.7	9.7	4	7.8

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	Z cm	Z1 cm
67509	32	35	1 1/4	90	6.8	11	4.2	9.1
67510	40	42	1 1/2	90	8	12.1	5	10.4
67511	50	54	2	90	10	15	6.5	13