
Geberit Mapress CuNiFe T-piece with female thread



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 0–3)
- For inert gases (e.g. nitrogen)
- For industry and shipbuilding
- For negative pressure

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	CuNi10Fe1.6Mn, material no. 2.1972.11

Art. no.	DN	d, ø mm	Rp "	d1, ø mm	arc °	L cm	L1 cm	l cm	l2 cm	z cm	z1 cm	z2 cm
67344	12 / 15 / 12	15	1/2	15	90	6.4	3.7	3.2	3.2	0.8	2.4	0.8
67347	20 / 15 / 20	22	1/2	22	90	7.4	4.1	3.7	3.7	1.6	2.8	1.6
67348	20	22	3/4	22	90	7.4	4.6	3.7	3.7	1.6	3.1	1.6
67349	25 / 15 / 25	28	1/2	28	90	8.4	4.4	4.2	4.2	1.9	3.1	1.9

Art. no.	DN	d, ø mm	Rp "	d1, ø mm	arc °	L cm	L1 cm	l cm	l2 cm	z cm	z1 cm	z2 cm
67350	25 / 20 / 25	28	3/4	28	90	8.4	4.6	4.2	4.2	1.9	3.1	1.9
67352	32 / 15 / 32	35	1/2	35	90	10	4.8	5	5	2.4	3.5	2.4
67353	32 / 20 / 32	35	3/4	35	90	10	5.3	5	5	2.4	4	2.4
67356	40 / 15 / 40	42	1/2	42	90	11.4	5.1	5.7	5.7	2.7	3.8	2.7
67357	40 / 20 / 40	42	3/4	42	90	11.4	5.6	5.7	5.7	2.7	4.3	2.7
67360	50 / 15 / 50	54	1/2	54	90	13.8	5.7	6.9	6.9	3.4	4.4	3.4
67361	50 / 20 / 50	54	3/4	54	90	13.8	6.2	6.9	6.9	3.4	4.9	3.4
67366	65 / 20 / 65	76.1	3/4	76.1	90	23	7	11.5	11.5	6.2	5.5	6.2
67369	80 / 20 / 80	88.9	3/4	88.9	90	26	7.6	13	13	7	6.1	7
67373	100 / 20 / 100	108	3/4	108	90	31	8.6	15.5	15.5	8	7.1	8