
Geberit Mapress CuNiFe bend adaptor 90° with male thread



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 0–3)
- For inert gases (e.g. nitrogen)
- For industry and shipbuilding
- For negative pressure

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	CuNi10Fe1.6Mn, material no. 2.1972.11

Art. no.	DN	d, ø mm	R "	arc °	L cm	H cm	Z cm
67515	12 / 15	15	1/2	90	3.8	7.2	1.8
67516	20 / 15	22	1/2	90	4.7	8.2	2.6
67517	20	22	3/4	90	4.7	8.6	2.6
67518	25	28	1	90	5.7	9.7	3.4

Art. no.	DN	d, ø mm	R "	arc °	L cm	H cm	Z cm
67519	32	35	1 1/4	90	6.8	11.2	4.2
67520	40	42	1 1/2	90	8	12.4	5
67521	50	54	2	90	10	14.4	6.5