
Geberit Mapress CuNiFe adaptor union with male thread





Example image

APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 0–3)
- For inert gases (e.g. nitrogen)
- For industry and shipbuilding
- For negative pressure

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Union nut made of brass
- Seal ring made of CIIR, black
- Flat gasket made of EPDM
- Pressing socket with transparent protection plug

TECHNICAL DATA

Medium temperature with flat gasket EPDM	0–100 °C
Product material	CuNi10Fe1.6Mn, material no. 2.1972.11

Art. no.	DN	d, ø mm	R "	G "	L cm	H cm
67232	12 / 15	15	1/2	3/4	8.1	6.1
67234	20 / 15	22	1/2	1	8.4	6.3
67243	20	22	3/4	1	8.5	6.4
67235	25	28	1	1 1/4	9.6	7.3

Art. no.	DN	d, ø mm	R "	G "	L cm	H cm
67236	32	35	1 1/4	1 1/2	10.4	7.8
67237	40	42	1 1/2	1 3/4	10.9	7.9
67238	50	54	2	2 3/8	12.4	8.9