

Geberit Mapress CuNiFe flange PN 10/16, with pressing socket



Example image





APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For seawater
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 0–3)
- For inert gases (e.g. nitrogen)
- For industry and shipbuilding
- For negative pressure

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug
- Design B1 (raised sealing strip with standard sealing strip), EN 1092-3

TECHNICAL DATA

Product material	CuNi10Fe1.6Mn, material no. 2.1972.11

ACCESSORIES

- Geberit bolt set for flange connection, made of CrNi steel
- Geberit flange gasket, fibre composite material PN 10/16

Art. no.	DN	d, ø mm	di, ø mm	D cm	k mm	m mm	L cm	l cm	Z cm	n pc.	PN bar
68692	15 / 12	15	14.1	9.5	65	14	6.1	1.2	4.1	4	10 / 16
68694	20	22	19	10.5	75	14	6.5	1.2	4.4	4	10 / 16
68695	25	28	25.2	11.5	85	14	6.9	1.2	4.6	4	10 / 16

Art. no.	DN	d, ø mm	di, ø mm	D cm	k mm	m mm	L cm	l cm	z cm	n pc.	PN bar
68696	32	35	32	14	100	18	7.2	1.4	4.6	4	10 / 16
68697	40	42	39	15	110	18	7.9	1.4	4.9	4	10 / 16
68698	50	54	51	16.5	125	18	8.7	1.6	5.2	4	10 / 16
68699	65	76.1	71.9	18.5	145	18	11.8	1.6	6.5	4	10 / 16
68700	80	88.9	84.7	20	160	18	12.5	1.8	6.5	8	10 / 16
68701	100	108	103.8	22	180	18	13	2	5.5	8	10 / 16