
Geberit Mapress Carbon Steel bend with plain end



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Outside zinc-plated
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	Non-alloy steel 1.0034 E195 (EN 10305)

INFO

- Dimension changes of individual articles as per table will be completed by end of May 2026

Art. no.	DN	d, ø mm	arc °	L cm	H cm	Z cm
20701	10	12	45	3.2	4.1	1.5
20702	12	15	45	2.8	3.6	0.8
20703	15	18	45	2.9	3.6	0.9
20704	20	22	45	3.2	4	1.1

GEBERIT

Art. no.	DN	d, ø mm	arc °	L cm	H cm	Z cm
20705	25	28	45	3.7	4.4	1.4
23706	32	35	45	4.3	5.3	1.7
23707	40	42	45	5.1	6.1	2.1
23708	50	54	45	6.2	7.3	2.7
20709	65	76.1	45	10.3	11.1	5
20710	80	88.9	45	11.7	12.8	5.7
20711	100	108	45	14.3	15.8	6.8
20301	10	12	90	3.1	4.5	1.4
20302	12	15	90	3.8	4.8	1.8
20303	15	18	90	4.2	5.1	2.2
20304	20	22	90	4.7	5.8	2.6
20305	25	28	90	5.7	6.3	3.4
23306	32	35	90	6.8	7.4	4.2

Art. no.	DN	d, ø mm	arc °	L cm	H cm	Z cm
23307	40	42	90	8	8.8	5
23308	50	54	90	10	10.8	6.5
20309	65	76.1	90	15.7	16.7	10.4
20310	80	88.9	90	18.4	19.5	12.4
20311	100	108	90	22.6	24.1	15.1