
Geberit Mapress Carbon Steel adaptor with male thread



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Outside zinc-plated
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	Non-alloy steel 1.0034 E195 (EN 10305)

Art. no.	DN	d, ø mm	R "	L cm	H cm
21701	10	12	3/8	3.3	1.6
21700	10 / 15	12	1/2	3.6	2.2
21702	12 / 10	15	3/8	3.8	1.8
21703	12 / 15	15	1/2	4.1	2.1
21714	12 / 20	15	3/4	4.3	2.6

Art. no.	DN	d, ø mm	R "	L cm	H cm
21704	15	18	1/2	4.2	2.2
21705	15 / 20	18	3/4	4.4	2.4
21715	20 / 15	22	1/2	4	2.2
21707	20	22	3/4	4.4	2.3
21716	20 / 25	22	1	4.6	2.6
21717	25 / 20	28	3/4	4.6	2.6
21708	25	28	1	4.8	2.5
21727	25 / 32	28	1 1/4	4.8	2.8
21719	32 / 25	35	1	5.1	2.5
21709	32	35	1 1/4	5.3	2.7
21720	32 / 40	35	1 1/2	5.3	3
21721	40 / 32	42	1 1/4	5.7	2.7
21710	40	42	1 1/2	5.7	2.7

Art. no.	DN	d, ø mm	R "	L cm	H cm
21722	50 / 40	54	1 1/2	7.1	3.6
21711	50	54	2	7.1	3.6
21712	65	66.7	2 1/2	11.8	4
21713	65	76.1	2 1/2	11.9	4.3
21724	80	88.9	3	13.7	5
21725	100	108	4	16	6.1