
Geberit Mapress Carbon Steel adaptor with female thread



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Outside zinc-plated
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	Non-alloy steel 1.0034 E195 (EN 10305)

Art. no.	DN	d, ø mm	Rp "	L cm	Z cm
21800	10	12	3/8	3.1	0.3
21801	10 / 15	12	1/2	3.4	0.4
21827	12 / 10	15	3/8	3.3	0.3
21802	12 / 15	15	1/2	3.7	0.4
21823	12 / 20	15	3/4	3.8	0.7

Art. no.	DN	d, ø mm	Rp "	L cm	Z cm
21803	15	18	1/2	3.7	0.4
21804	15 / 20	18	3/4	3.8	0.3
21805	20 / 15	22	1/2	3.8	0.3
21806	20	22	3/4	3.9	0.3
21824	20 / 25	22	1	4.2	0.4
21807	25 / 15	28	1/2	3.8	0.2
21808	25 / 20	28	3/4	3.8	0.1
21809	25	28	1	4.4	0.4
21810	32 / 20	35	3/4	4.2	0.1
21820	32 / 25	35	1	4.5	0.2
21811	32	35	1 1/4	4.9	0.4
21814	40	42	1 1/2	5.3	0.4
21818	50	54	2	6.2	0.5