
# Geberit Mapress Copper T-piece, reduced



Example image




## APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)
- For technical building systems, industry and shipbuilding

## CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed up to ø ≤ 54 mm
- Seal ring made of CIIR, black, up to ø ≤ 54 mm
- Seal ring made of EPDM, black, from ø > 54 mm
- Pressing socket with transparent protection plug

## TECHNICAL DATA

| | |
|---|---|
| Product material | Cu-DHP copper CW024A (EN 1412) |

| Art. no. | DN | d, ø mm | d1, ø mm | d2, ø mm | arc ° | L cm | L1 cm | l cm | l2 cm | z cm | z1 cm | z2 cm |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **61243** | 12 / 10 / 10 | 15 | 12 | 12 | 90 | 6.7 | 3.3 | 3.2 | 3.5 | 2 | 1.6 | 1.7 |
| **61252** | 12 / 10 / 12 | 15 | 12 | 15 | 90 | 6.4 | 3.3 | 3.2 | 3.2 | 1.2 | 1.6 | 1.2 |
| **61104** | 12 / 20 / 12 | 15 | 22 | 15 | 90 | 7.4 | 3.4 | 3.7 | 3.7 | 1.7 | 1.3 | 1.7 |
| **61253** | 15 / 10 / 15 | 18 | 12 | 18 | 90 | 6.8 | 3.5 | 3.4 | 3.4 | 1.4 | 1.8 | 1.4 |

GEBERIT

| Art. no. | DN | d, ø mm | d1, ø mm | d2, ø mm | arc ° | L cm | L1 cm | l cm | l2 cm | z cm | z1 cm | z2 cm |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **61235** | 15 / 12 / 12 | 18 | 15 | 15 | 90 | 7.4 | 3.5 | 3.4 | 4 | 1.4 | 1.5 | 2 |
| **61254** | 15 / 12 / 15 | 18 | 15 | 18 | 90 | 6.8 | 3.5 | 3.4 | 3.4 | 1.4 | 1.5 | 1.4 |
| **61236** | 15 / 15 / 12 | 18 | 18 | 15 | 90 | 7.4 | 3.4 | 3.4 | 4 | 1.4 | 1.4 | 2 |
| **61244** | 20 / 10 / 20 | 22 | 12 | 22 | 90 | 7.4 | 3.5 | 3.7 | 3.7 | 2.1 | 1.7 | 2.1 |
| **61240** | 20 / 12 / 12 | 22 | 15 | 15 | 90 | 8 | 3.8 | 3.7 | 4.3 | 1.6 | 1.8 | 2.3 |
| **61256** | 20 / 12 / 20 | 22 | 15 | 22 | 90 | 7.4 | 3.8 | 3.7 | 3.7 | 1.6 | 1.8 | 1.6 |
| **61257** | 20 / 15 / 20 | 22 | 18 | 22 | 90 | 7.4 | 3.8 | 3.7 | 3.7 | 1.6 | 1.8 | 1.6 |
| **61242** | 20 / 20 / 12 | 22 | 22 | 15 | 90 | 7.4 | 3.7 | 3.7 | 4.5 | 1.6 | 1.6 | 2.5 |
| **61259** | 25 / 12 / 25 | 28 | 15 | 28 | 90 | 8.4 | 4.1 | 4.2 | 4.2 | 1.9 | 2.1 | 1.9 |
| **61260** | 25 / 15 / 25 | 28 | 18 | 28 | 90 | 8.4 | 4.1 | 4.2 | 4.2 | 1.9 | 2.1 | 1.9 |
| **61261** | 25 / 20 / 25 | 28 | 22 | 28 | 90 | 8.4 | 4.1 | 4.2 | 4.2 | 1.9 | 2 | 1.9 |
| **61212** | 32 / 12 / 32 | 35 | 15 | 35 | 90 | 10 | 5.1 | 5 | 5 | 2.4 | 3.1 | 2.4 |
| **61213** | 32 / 15 / 32 | 35 | 18 | 35 | 90 | 10 | 5 | 5 | 5 | 2.4 | 3 | 2.4 |

GEBERIT

| Art. no. | DN | d, ø mm | d1, ø mm | d2, ø mm | arc ° | L cm | L1 cm | l cm | l2 cm | z cm | z1 cm | z2 cm |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **61214** | 32 / 20 / 32 | 35 | 22 | 35 | 90 | 10 | 5.2 | 5 | 5 | 2.4 | 3.1 | 2.4 |
| **61215** | 32 / 25 / 32 | 35 | 28 | 35 | 90 | 10 | 5.5 | 5 | 5 | 2.4 | 3.2 | 2.4 |
| **61229** | 40 / 12 / 40 | 42 | 15 | 42 | 90 | 11.4 | 5.4 | 5.7 | 5.7 | 2.7 | 3.4 | 2.7 |
| **61217** | 40 / 15 / 40 | 42 | 18 | 42 | 90 | 11.4 | 5.4 | 5.7 | 5.7 | 2.7 | 3.4 | 2.7 |
| **61218** | 40 / 20 / 40 | 42 | 22 | 42 | 90 | 11.4 | 5.5 | 5.7 | 5.7 | 2.7 | 3.4 | 2.7 |
| **61219** | 40 / 25 / 40 | 42 | 28 | 42 | 90 | 11.4 | 5.8 | 5.7 | 5.7 | 2.7 | 3.5 | 2.7 |
| **61220** | 40 / 32 / 40 | 42 | 35 | 42 | 90 | 11.4 | 6.2 | 5.7 | 5.7 | 2.7 | 3.6 | 2.7 |
| **61227** | 50 / 20 / 50 | 54 | 22 | 54 | 90 | 13.8 | 6.1 | 6.9 | 6.9 | 3.4 | 4 | 3.4 |
| **61228** | 50 / 25 / 50 | 54 | 28 | 54 | 90 | 13.8 | 6.4 | 6.9 | 6.9 | 3.4 | 4.1 | 3.4 |
| **61225** | 50 / 32 / 50 | 54 | 35 | 54 | 90 | 13.8 | 6.8 | 6.9 | 6.9 | 3.4 | 4.2 | 3.4 |
| **61226** | 50 / 40 / 50 | 54 | 42 | 54 | 90 | 13.8 | 7.2 | 6.9 | 6.9 | 3.4 | 4.2 | 3.4 |
| **61280** | 65 / 20 / 65 | 66.7 | 22 | 66.7 | 90 | 22 | 6.5 | 11 | 11 | 6 | 4.4 | 6 |
| **61281** | 65 / 25 / 65 | 66.7 | 28 | 66.7 | 90 | 22 | 6.8 | 11 | 11 | 6 | 4.5 | 6 |

| Art. no. | DN | d, ø mm | d1, ø mm | d2, ø mm | arc ° | L cm | L1 cm | l cm | l2 cm | z cm | z1 cm | z2 cm |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **61282** | 65 / 50 / 65 | 66.7 | 54 | 66.7 | 90 | 22 | 8.2 | 11 | 11 | 6 | 4.7 | 6 |
| **61283** | 65 / 20 / 65 | 76.1 | 22 | 76.1 | 90 | 23 | 7.2 | 11.5 | 11.5 | 6.2 | 5.1 | 6.2 |
| **61284** | 65 / 32 / 65 | 76.1 | 35 | 76.1 | 90 | 23 | 7.9 | 11.5 | 11.5 | 6.2 | 5.3 | 6.2 |
| **61285** | 65 / 40 / 65 | 76.1 | 42 | 76.1 | 90 | 23 | 8.3 | 11.5 | 11.5 | 6.2 | 5.3 | 6.2 |
| **61286** | 65 / 50 / 65 | 76.1 | 54 | 76.1 | 90 | 23 | 8.9 | 11.5 | 11.5 | 6.2 | 5.4 | 6.2 |
| **61287** | 65 / 65 / 65 | 76.1 | 66.7 | 76.1 | 90 | 23 | 11 | 11.5 | 11.5 | 6.2 | 6 | 6.2 |
| **61288** | 80 / 20 / 80 | 88.9 | 22 | 88.9 | 90 | 26 | 7.8 | 13 | 13 | 7 | 5.7 | 7 |
| **61289** | 80 / 40 / 80 | 88.9 | 42 | 88.9 | 90 | 26 | 8.9 | 13 | 13 | 7 | 5.9 | 7 |
| **61290** | 80 / 50 / 80 | 88.9 | 54 | 88.9 | 90 | 26 | 9.5 | 13 | 13 | 7 | 6 | 7 |
| **61292** | 80 / 65 / 80 | 88.9 | 76.1 | 88.9 | 90 | 26 | 11.6 | 13 | 13 | 7 | 6.3 | 7 |
| **61293** | 100 / 20 / 100 | 108 | 22 | 108 | 90 | 31 | 8.8 | 15.5 | 15.5 | 8 | 6.7 | 8 |
| **61294** | 100 / 50 / 100 | 108 | 54 | 108 | 90 | 31 | 10.5 | 15.5 | 15.5 | 8 | 7 | 8 |
| **61295** | 100 / 65 / 100 | 108 | 66.7 | 108 | 90 | 31 | 12.6 | 15.5 | 15.5 | 8 | 7.6 | 8 |

| Art. no. | DN | d, ø mm | d1, ø mm | d2, ø mm | arc ° | L cm | L1 cm | l cm | l2 cm | z cm | z1 cm | z2 cm |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **61296** | 100 / 65 / 100 | 108 | 76.1 | 108 | 90 | 31 | 12.6 | 15.5 | 15.5 | 8 | 7.3 | 8 |
| **61297** | 100 / 80 / 100 | 108 | 88.9 | 108 | 90 | 31 | 13.7 | 15.5 | 15.5 | 8 | 7.7 | 8 |