
Geberit Mapress Copper adaptor socket



Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For connecting non-system copper pipe diameters
- For transitions from copper pipes to mild steel pipes
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- ø 14 mm to be pressed with Geberit Mapress pressing jaw ø 15 mm
- ø 16 mm should be pressed with the Geberit Mapress pressing jaw ø 18 mm
- Seal ring made of CIIR, black
- O-ring made of EPDM
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	Lead-free gunmetal

Art. no.	DN	d, ø mm	d1, ø mm	L cm	Z cm
These articles are suitable for the following system: **Geberit Mapress Therm**					
62020	12	15	14	4.1	0.1
62022	12	15	16	4.1	0.1
62024	15	18	16	4.1	0.1

Art. no.	DN	d, ø mm	d1, ø mm	L cm	z cm
These articles are suitable for the following system: **Geberit Mapress Copper**					
62020	12	15	14	4.1	0.1
62022	12	15	16	4.1	0.1
62024	15	18	16	4.1	0.1