
Geberit Mapress Copper elbow adaptor 90° with female thread


Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	Lead-free gunmetal

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	Z cm	Z1 cm
63860	10	12	3/8	90	3.2	2.3	1.5	1.3
63861	10 / 15	12	1/2	90	3.4	2.4	1.7	1.1
63862	12 / 10	15	3/8	90	3.3	2.4	1.3	1.4
63853	12 / 15	15	1/2	90	3.6	2.7	1.6	1.4
63854	15	18	1/2	90	3.6	3	1.6	1.7

Art. no.	DN	d, ø mm	Rp "	arc °	L cm	L1 cm	Z cm	Z1 cm
63863	15 / 20	18	3/4	90	3.8	3.1	1.8	1.6
63864	20 / 15	22	1/2	90	3.8	3.2	1.7	1.9
63855	20	22	3/4	90	4.5	2.7	2.4	1.2
63856	25	28	1	90	5.1	3.3	2.8	1.6
63857	32	35	1 1/4	90	5.5	4.5	2.9	2.6
63865	40	42	1 1/2	90	6.7	5.2	3.7	3.3
63866	50	54	2	90	7.4	6	3.9	3.7